KATANA

ATV



100% SYNTHÉTIC

SPORT

API SP / JASO MA2

PAO & ESTER TECHNOLOGY

Available viscosity grades :

5W-40 / 10W-40 / 15W-50

KATANA ATV is a 100% synthetic 4-stroke quad and SSV engine oil made of high-quality polyalphaolefins (PAOs), esters and additives. Designed to offer very high off-road performance, it guarantees maximum protection under heavy load and excellent clutch control. It promotes sharper revs and smooth, fast gear changes.

PACKING UNITS :



TECHNICAL DATA :

TEST	METHOD	TYPICAL VALUES			MEASURE UNITS
		5W-40	10W-40	15W-50	
Density at 20°C	ASTM D4052	0,853	0,867	0,859	g/cm^3
Viscosity at 40°C	ASTL D445 or ASTM D7279	80,2	86	125,7	Mm^2/s
Viscosity at 100°C	ASTL D445 or ASTM D7279	13,27	13,82	18,3	Mm^2/s
Viscosity Index (VIE)	ASTM D2270	168	169	163	-
Pour point	ASTM D97	-45	-42	-42	°C
Flash point	ASTM D92	236	252	260	°C
TBN	ASTM D2896	7,1	7,4	7,1	mg KOH/g